



Seagate® Nytro™ WarpDrive™ Application Acceleration Cards Hardware Compatibility List

This represents basic compatibility and is only a guide to hardware which is known to function with Seagate® Nytro™ WarpDrive™ application acceleration cards

Updated 08/26/2014
Servers/Motherboards

Seagate Server Qualification and Interop Lab performs comprehensive functionality testing in order to demonstrate compatibility of Seagate® Nytro™ WarpDrive™ series applications acceleration cards. The listed components represent the compatibility guide for the ecosystem based on our findings. Testing consists individual test cases on specific servers and motherboards.

Seagate® Nytro™ WarpDrive™ Acceleration Application Cards

Product	Model	Capacity	Form Factor	Firmware Package
NWD-BLP4-800	ST800KN0012	800GB	Half Height, Half Length	12.00.02.00
NWD-BLP4-1600	ST1600KN0002	1.6TB	Half Height, Half Length	12.00.02.00
NWD-BFH6-1200	ST03-25614-00	1.2TB	Full Height, Half Length	12.00.02.00
NWD-BFH8-1600	ST03-25615-00	1.6TB	Full Height, Half Length	12.00.02.00
NWD-BFH8-3200	ST03-25614-00	3.2TB	Full Height, Half Length	12.00.02.00

Nytro WarpDrive products are tested against a broad compatibility list of motherboards and servers. In order to operate at full capability, Nytro WarpDrive requires thermal and power specification be supported and maintained. Please refer to the Thermal, Atmospheric, and Electrical Characteristics for your Nytro WarpDrive in the User Guide for these power and thermal requirements.

Seagate® Nytro™ WarpDrive™ Acceleration Application Cards Hardware Compatibility List

Servers				
Manufacture	Model /Family	System BIOS	CPU Information	Chipset
Cisco	UCS C240 M3	C240M3.1.5.1c.0	Intel Xeon E5-2680, @ 2.70 Ghz	Intel C602
	UCS B200 M3	B200m3.2.0.3.0.051620121210	Intel Xeon E5-2620, @ 2.0Ghz	Intel C600
	UCS B22 M3	B22M3.2.0.3a.0.051820121158	Intel Xeon E5-2450, @ 2.1 Ghz	Intel C600
	UCS B420 M3	B420M3.2.0.2.04.061120121226	Intel Xeon E5-4650, @ 2.7 Ghz	Intel C600
	UCS C210 M2	C200.1.4.1.0.0771320110702	Intel Xeon E5649, @ 2.53 Ghz	Intel 5520
DELL	PowerEdge R920	1.07	Intel Xeon E7-2880, @ 2.50GHz	Intel C602
	PowerEdge R820	2.0.21	Intel Xeon E5-4640, @ 2.40GHz	Intel C600
	PowerEdge R720xd	2.0.19	Intel Xeon E5-2630, @2.6GHz	Intel C600
	PowerEdge R720	1.2.6	Intel Xeon E5-4607, @ 2.2 GHz	Intel C600
	PowerEdge R720	1.2.6	Intel Xeon E5-2630, @ 2.30 GHz	Intel C600
	PowerEdge R620	1.2.6	Intel Xeon E5-2620, @ 2.00GHz	Intel C600
	PowerEdge R710	6.1.0	Intel Xeon E5507, @2.26GHz	Inte 5520
	PowerEdge R715	2.3.0	AMD Opteron 6204, @ 3.3GHz	AMD SR5690 / SP5100
	PowerEdge T710	6.1.0	Intel® Xeon® E5530, @2.40GHz	Inte 5520
	PowerEdge R805	3.0.2	AMD Opteron 2350, @2.0GHz	NVIDIA MCP55Pro
	PowerEdge R810	2.5.0	Intel Xeon, @2.26GHz	Intel 7500 Chipset
	PowewrEdge 815	2.3.0	AMD Opteron 6168, @1.9 Ghz	AMD SR5650
	PowewrEdge 2950	6.1.0	Intel Xeon E5640, @ 2.67GHz	Intel 5000X
Echostreams	FlacheSAN2	SE5C600.86B.01.06.0001	Intel Xeon E5-2650 @ 2GHz	Intel C600
HP	Proliant DL380e G8	P73	Intel Xeon E5-2440 v2, @ 1.90GHz	Intel C600
	Proliant DL380P G8	P70	Intel Xeon E5-2670, @2.6GHz	Intel C600
	Proliant DL385 G8	A28	AMD Opteron 6234, @ 2.4GHz	AMD SR5690/SP5100
	Proliant DL380 G7	P67	Intel Xeon E5-5620, @ 2.40 GHz	Intel 5520
	DL180 G6	620	Intel Xeon X5560, @ 2.80GHz	Intel 5520
	DL380 G6	P62	Intel Xeon E5540, @ 2.53 GHz	Intel 5520
	DL380 G7	P67	Intel Xeon X5650, @ 2.67 GHz	Intel 5520
	DL380 G8	P70	Intel E5-2600 Series	Intel C600 Series
	DL585 G7	A16	AMD Opteron 6136, @ 2.4 GHz	AMD SR5690

Nytro WarpDrive products are tested against a broad compatibility list of motherboards and servers. In order to operate at full capability, Nytro WarpDrive requires thermal and power specification be supported and maintained. Please refer to the Thermal, Atmospheric, and Electrical Characteristics for your Nytro WarpDrive in the User Guide for these power and thermal requirements.

Seagate® Nytro™ WarpDrive™ Acceleration Application Cards Hardware Compatibility List

Servers				
Manufacture	Model /Family	System BIOS	CPU Information	Chipset
IBM	xSeries 3650 M4	1.60	Intel Xeon E5-2609, @ 2.40GHz	Intel C602
	xSeries 3630 M4	1.30	Intel Xeon E5-2430, @ 2.20GHz	Intel C600
	xSeries 3550 M4 Dong Shan	Y5E112HUS-1.37	Intel Xeon E5-2609, @ 2.4 Ghz	Intel C604
	xSeries 3650 M4	1.21	Intel Xeon E5-2609, @ 2.4 GHz	Intel C600
	xSeries 3690 M5 megalon	MLE173BUS-1.73	Intel Xeon E7-2803, @ 1.73GHz	IBM EX5
	xSeries 3850 M4 Ghidorah	G0E173BUS-1.73	Intel Xeon E7-4830, @ 2.1 Ghz	IBM EX5
	xSeries 3550 M3	1.14	Intel Xeon E5607, @ 2.27 GHz	Intel 5520
Intel	S2600IP	SE5C600.86B.01.06.0001	Intel Xeon E5-2650 @ 2GHz	Intel C600
	S2600G(Z/L)	SE5C600.86B.01.03.002	Intel Xeon E5-2670, @ 2.6GHz	Intel C602
	S5520UR	86B.01.00.00.49	Intel Xeon X5680, @ 3.33GHz	Intel 5520
	S5520UR	86B.01.00.00.30	Intel Xeon L5520, @ 2.27GHz	Intel 5520
Lenovo	RD430	2.05	Intel Xeon E5-2607, @ 2.2 GHz	C602J
	RD630	2.05	Intel Xeon E5-2609, @ 2.4 GHz	C602
	RD830	SE5C600.86B.01.02.0015	Intel Xeon E5-2609, @ 2.4 GHz	C602
	TD530	2.03	Intel Xeon E5-2609, @ 2.40 GHz	Intel C602J
	TD330	2.01	Intel Xeon E5-2407, @ 2.20 GHz	Intel C600
OCP	Windmill Servers	4.6.4.1	Intel Xeon E5-2670, @ 2.6 Ghz	Intel C602
Oracle	x4270 M2	08.12.01.03	Intel Xeon X5675, @ 3.07Ghz	Intel 5520
	x4270 M3	2.14.1219	Intel Xeon E5 -2660, @ 2.2 Ghz	Intel C600
	T4-1	8.1.4.e	SPARC T4	SPARC T4
	T4-2 (SPARC)	8.1.4.e	SPARC T4	SPARC T4
Supermicro	CSE113TQ-563CB	3.00	Intel Xeon E5-2630L v2, @ 2.40 GHz	Intel C602
	SYS-7047R-TXRF	3.00	Intel Xeon E5-2640 @ 2.50GHz	Intel C602
	SYS-6027TR-DTRF (Fat-Twin)	3.00	Intel Xeon-E5 2609 @ 2.40GHz	Intel C602
	SYS-6027R-3RF4+	2.00	Intel Xeon E5-2609 @ 2.40 GHz	Intel C606
	SYS-7047A-T	1.0b	Intel Xeon E5-2603 @ 1.80 GHz	Intel C602
	6027R-WRF	1.0b	Intel Xeon E5-2667 XC @ 2.9GHz	Intel C602

Nytro WarpDrive products are tested against a broad compatibility list of motherboards and servers. In order to operate at full capability, Nytro WarpDrive requires thermal and power specification be supported and maintained. Please refer to the Thermal, Atmospheric, and Electrical Characteristics for your Nytro WarpDrive in the User Guide for these power and thermal requirements.

Seagate® Nytro™ WarpDrive™ Acceleration Application Cards Hardware Compatibility List

Motherboards				
Manufacture	Model /Family	System BIOS	CPU Information	Chipset
ASUS	Q87M-E/CSM	0906	Intel Core i5-4570, @ 3.20GHz	Intel Q87
	Z87-PRO (rev 1.02)	1504	Intel Core i5-4570, , @ 3.20GHz	Intel Z87
	Z9PE-D8WS (rev 1.04)	0703	Intel Xeon E5-2603, @ 1.8GHz	Intel C602
	Sabertooth 990FX (rev 1.01)	0901	AMD FX6100, @ 3.30GHz	AMD 990FX/SB950
	P6T6 WS Revolution	0001	Intel Core i7 950, @ 3.07GHz	Intel X58 Express
	P6 X58-E WS	0206	Intel Xeon W5580 @ 3.2GHz	Intel X58
	P8BWS (rev 1.01)	0511	Intel Xeon E31245 @ 3.30GHz	Intel C206
	P8B-M (rev 1.01)	0701	Intel Xeon E3-1225 @ 3.10GHz	Intel C204
EVGA	Classified 4-Way SLI	6.00 PG	Intel Xeon E5520, @ 2.27GHz	Intel X58
	Classified SR-2	080016	Intel Xeon E5625, @ 2.40GHz	Intel 5520
Gigabyte	GA-Z87X-UD3H (rev 1.0)	F7	Intel Core i5-4570, @ 3.20GHz	Intel Z87 Express
	GA-X79S-UP5-WIFI (rev 1.0)	F3	Intel Core i7-3820, @ 3.60 GHz	Intel C606 Express
	GA-F2A85X-UP4 (rev 1.0)	F3	AMDA4-5300, @ 3.4Ghz	AMD A85X
	Z68A-D3H-B3 (rev 1.3)	F13	Intel Core i5 2550, @3.30GHz	Intel Z68
	GA-X79-UD3 (rev 1.0)	F8	Intel Xeon E5-2603, @ 1.8GHz	Intel X79
	GA-990FXA-UD7 (rev 1.1)	F7	AMD FX6100, @ 3.30GHz	AMD 990FX/SB950
	GA-Z68A-D3H-B3 (rev 1.3)	F12	Intel Core i32120, @ 3.30GHz	Intel Z68
GA-X58A-UD9 (rev 1.0)	F4	Intel Xeon E5520, @ 2.27GHz	X58	
Intel	S2600IP	SE5C600.86B.01.06.0001	Intel Xeon E5-2650 @ 2GHz	Intel C600
	S2600G(Z/L)	SE5C600.86B.01.03.002	Intel Xeon E5-2670, @ 2.6GHz	Intel C602
	S5520UR	86B.01.00.00.49	Intel Xeon X5680, @ 3.33GHz	Intel 5520
	S5520UR	86B.01.00.00.30	Intel Xeon L5520, @ 2.27GHz	Intel 5520

Nytro WarpDrive products are tested against a broad compatibility list of motherboards and servers. In order to operate at full capability, Nytro WarpDrive requires thermal and power specification be supported and maintained. Please refer to the Thermal, Atmospheric, and Electrical Characteristics for your Nytro WarpDrive in the User Guide for these power and thermal requirements.

Seagate® Nytro™ WarpDrive™ Acceleration Application Cards Hardware Compatibility List

Motherboards / Servers

Manufacture	Model /Family	System BIOS	CPU Information	Chipset
Supermicro	X10SLM-F	1.1b	Intel Xeon E3-1220v3, @ 3.10 GHz	Intel C224 Express
	X9DRH-7F	3.0	Intel Xeon E5-2630L v2, @ 2.40 GHz	Intel C602
	X9DRX+-F	3.0	Intel Xeon E5-2640 @2.5GHz	Intel C602
	X9DRT-HF	3.0	Intel Xeon-E5 2609 @ 2.40GHz	Intel C602
	X9SRA	3.0a	Intel Xeon E5-2640, @ 2.50GHz	Intel C602
	X9DRD-7LN4F	2.00	Intel Xeon E5-2650, @ 2.0GHz	Intel C602J
	X9DAi (rev 1.02)	1.0b	Intel Xeon E5-2603, @ 1.80 GHz	Intel C602
	X9DR3-LN4F+ (rev 1.10)	2.00	Intel Xeon E5-2609, @ 2.40 GHz	Intel C606
	X9SRE (rev 1.2)	1.0c	Intel Xeon E5-1620, @ 3.60 GHz	Intel C602
	X9DRI-F	1.1	Intel Xeon E5-2680, @ 2.70GHz	Intel C602
	X9DRW-iF	1.0b	Intel Xeon E5-2667 XC, @ 2.9GHz	Intel C602
	X8DTU-F	2.1	Intel Xeon x5650, @ 2.67GHz	Intel 5520
	X8DT3-F	2.0c	Intel Xeon E5520, @ 2.27GHz	Intel 5520
	X8STE	2.0c	Intel Xeon E5520, @ 2.00GHz	Intel X58 Express
	X8DAi	2.0c	Intel Xeon W5580, @ 3.2GHz	Intel 5520
	X8DA3	2.0c	Intel Xeon E5520, @ 2.27 GHz	Intel 5520
	X8DT6	2.0b	Intel Xeon E5606, @2.16GHz	Intel 5520
	X8DTH-i	2.1a	Intel Xeon E5620, @ 2.4GHz	Intel 5520
	X8DAH	2.0a	Intel Xeon E5620, @ 2.4GHz	Intel 5520
	H8DG6	2.0a	AMD Opteron 6168, @ 1.9GHz	AMD SR5690 / SP5100
TYAN	S7050GM4NR	V1.02i	Intel Xeon E5 2603, @ 1.80GHz	Intel C602
	S7053WGM2NR	V1.03F	Intel Xeon E5 2603, @ 1.80GHz	Intel C602
	S7056WGM3NR-B	V 1.01B	Intel Xeon E5 2609, @ 2.40GHz	Intel C602
	S7010AGM2NRF	3.02	Intel Xeon W5580, @ 3.2GHz	Intel 5520
	S7012GM4NR	2.3	Intel Xeon W5580, @ 3.2GHz	Intel 5520
	S7025AGM2NR	American MegaTrend V1.05	Intel Xeon E5520, @ 2.27GHz	Intel 5520
	S7002G2NR-LE	American MegaTrend V1.07	Intel CPU @ 2.80GHz	Intel 5500
	S8230GM4NR	American MegaTrend V2.04	AMD Opteron 6168, @ 1.90GHz	AMD SR5690
	S5211	V1.09	Intel Xeon X3220, @ 2.66GHz	S3200/S3210
	S5512WGM2NR (rev 1.01)	1.05a	Intel Xeon E3-1225, @ 3.10GHz	Intel C204
	S5510G2NR-LE	1.03	Intel Xeon E3-1245, @ 3.30GHz	Intel® C202

Nytro WarpDrive products are tested against a broad compatibility list of motherboards and servers. In order to operate at full capability, Nytro WarpDrive requires thermal and power specification be supported and maintained. Please refer to the Thermal, Atmospheric, and Electrical Characteristics for your Nytro WarpDrive in the User Guide for these power and thermal requirements.